

Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

SAS-510-4 Log Periodic Antenna 290 MHz – 4 GHz

This Broadband Log Periodic Antenna is an ideal solution for radiated emissions and normalized site attenuation.





Frequency Range: 290 MHz - 4000 MHz Antenna Factor: 15 - 37 dB Gain: 6.2 dBi Maximum Continuous Power: 1000 Watts Maximum Radiated Field: 200 V/m Pattern Type: directional 3dB Beamwidth (E-Field): 41° 3dB Beamwidth (H-Field): 100° Impedance: 50 Ω VSWR: 1.65:1 typ. (2.5:1 max) Connector: N-Type, Female Mounting Base: ¼ x 20 Thread, Female


Features

- Frequency Range of 290 MHz to 4000 MHz
- Receive and Transmit
- Individually Calibrated (1, 3 and 10 Meter calibration included, horizontal polarization)
- Rugged Construction
- Three Year Warranty

The A.H. Systems' SAS-510-4 antenna is lightweight, compact and has been manufactured to ensure maximum gain, low VSWR and high power handling capabilities. Whether testing inside a shielded enclosure or outdoors, this antenna will display efficient performance characteristics through its frequency range.

Recommended Accessories

- ATU-510 (Antenna Tripod, Wooden)
- AEH-510 (Azimuth and Elevation Head)
- PAM-0204 (22 dB Preamplifier)






Tel: (818) 998-0223 Fax: (818) 998-6892

٠

sales@AHSystems.com www.AHSystems.com



Physical Dimensions

Length:	23.8 in. <i>(60.4 cm)</i>
Width:	20.1 in. (51.1 cm)
Weight:	1.5 lb.'s <i>(0.68 kg)</i>