



PA 5740 POWER AMPLIFIER/BATTERY SIMULATOR



Battery simulators replace the vehicle battery in the test environment. These sources must fulfill various criteria concerning power rating, voltage, slew rate, impedance, etc. depending on the particular application. Bipolar current sources are specified for in several cases. Pulse 2b, pulse 4, sine wave noise and other complex simulations are realm of the PA 5740. Of course the amplifier is also perfectly suited for ISO 7637 compliant simulated conducted transient testing. Offering combinations of features that exist in no other battery simulator, the PA 5740 series is the right product at the right price for your EMC needs.

- **Capacitive stability mode**
- **High bandwidth up to 180 kHz**
- **Fast slew rate**
- **Ideal for use as synchronized auxiliary channels required by various EMC standards**
- **Two gain settings for universal use**
- **Sense lines for cable voltage drop compensation**
- **Four quadrant operation**
- **Banana output connector on both the front and back of the simulator**

Designed specifically for automotive EMC testing, Teseq's 42 V ready amplifier sets the pace for automotive battery simulation including features necessary for automotive immunity testing such as sense wires for cable voltage drop compensation and several operating modes for stability with complex automotive loads.

For more details, see the complete catalog "Automotive Electrical Disturbances".

Teseq AG
Nordstrasse 11F 4542 Luterbach Switzerland
T +41 32 681 40 40 F +41 32 681 40 48
sales@teseq.com www.teseq.com

© February 2011 Teseq®
Specifications subject to change without notice.
Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.