

rf/microwave instrumentation

Model ATH4G8, M1, M2 Antenna 4 GHz-8GHz

The Model ATH4G8 is a wide band, high gain, microwave horn antenna that provides a minimum gain of 11.5dB over isotropic. The Model ATH4G8 supplies the constant high intensity fields necessary for RFI/EMI field testing within and beyond the confines of a shielded room. A removable gain enhancer is included to insure the required field strength when conducting 3 meter testing. The Model ATH4G8 is compact and light weight for ready mobility, yet is built tough enough for the extra demands of outdoor use and easily mounts on a tripod. Part of a family of microwave frequency antennas the Model ATH4G8 provides the 4-8GHz response required for many often-used test specifications.

SPECIFICATIONS

FREQUENCY RANGE	4-8GHz
POWER INPUT (maximum)	See Model Configuration
POWER GAIN (over isotropic)	See Curve See Curve
IMPEDANCE	50 ohms nominal
VSWR Maximum Average	
BEAM WIDTH (average) E Plane	
FRONT TO BACK RATIO (minimum)	20 dB
CONNECTOR	See Model Configuration
MOUNTING PROVISIONS	May also be tripod mounted in two perpendicular planes using optional tripod.
WEIGHT (with enhancer)	2.27 kg (5.0 lbs)
SIZE (WxHxD) (without gain enhancer)(with gain enhancer)	

MODEL CONFIGURATIONS

Model Number	Connector	Power
ATH4G8	N(F)	500 watts
ATH4G8M1	SMA(F)	120 watts
ATH4G8M2	7-16(F)	1200 watts (15kW peak pulse @ 8GHz)





