Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

ATU-514
Antenna Tripod
Sturdy rugged design

The ATU-514 Antenna tripod is a non-metallic tripod used to position, support, and stabilize most compliance test antennas.



Features

- Non-metallic, non-reflective
- Easy height adjustments
- Standard 1/4-20 mounting thread
- Lightweight and durable rugged construction

We're excited to unveil our new ATU-514 "non-magnetic and non-reflective" antenna tripod, a brand-new product made especially for compliance testing. This collapsible tripod is built with all non-metallic materials that will not influence your antenna measurements. The ATU-514 is a nononsense antenna tripod that offers up to 50lbs (22.6Kg) load capacity and has telescoping legs with an adjustable center mast to achieve heights up to 2 meters.

Maximum Height: 79" (2 meters)
Minimum Height: 33.5" (85 cm)
Minimum Height
... 4" (10 cm)

(with center post flipped): 4" (10 cm)

footprint radius: 25" (63.5 cm) with legs fully extended 15" (38 cm) with legs colapsed

Maximum Load: 50 lbs. (22.6 Kg)

Folded Dimensions: 37" x 5.5" x 5.5" (940 x 140 x 140mm)

Weight: 6.2 lbs. (2.8 Kg)

Related Products

- AEH-510 Azimuth and Elevation Head, Nylon
- AEH-511 Azimuth and Elevation Head, Metal
- VER-60 60" extension rod
- BTE-510 Bilogical Antenna Tripod Extension, Fiberglass