

Tel: (818) 998-0223 ◆ sale Fax: (818) 998-6892 ◆ w

sales@AHSystems.com www.AHSystems.com

TV-2 Tuned Dipole Antenna 325 MHz – 1 GHz

Designed per the FCC specifications, this Tuned Dipole Antenna is ideal for broadcast field measurements.





Frequency Range: 325 MHz - 1000 MHz Balun Loss: <0.5 dB Maximum Continuous Power: 60 Watts Impedance: 50 Ω Connector: N-Type, Female

Features

- F.C.C. Antenna Balun Design
- Omni-directional, Receive and Transmit
- Individually Calibrated (1, 3 and 10 Meter calibration included, horizontal polarization)
- Rugged Construction with low balun loss, low VSWR
- FCC Balun Design
- Three Year Warranty

The A.H. Systems' TV-2 antenna provides an accurate standard for precise EMI and site attenuation measurements (per OET-55 and ANSI C63.5). The TV-2 is manufactured per the FCC balun design and individually calibrated.

Recommended Accessories

- ATU-510 (Antenna Tripod, Wooden)
- AEH-510 (Azimuth and Elevation Head)
- PAM-0202 (30 dB Preamplifier)
- SAC-213 (3 Meter N/N cable)



Tel: (818) 998-0223 ◆ Fax: (818) 998-6892 ◆ sales@AHSystems.com www.AHSystems.com

