## R&S®HL024S8 Crossed Log-Periodic Antenna

1 GHz to 18 GHz

Log-periodic directional antenna consisting of the R&S®HL024A1 and two broadband preamplifiers for horizontal and vertical polarization





The R&S°HL024S8 consists of the R&S°HL024A1 crossed log-periodic antenna and two broadband preamplifiers. It is suitable for the reception of linearly polarized waves.

Two RF connectors are provided for simultaneous use of both polarization planes.

The preamplifiers can be optionally switched on. They prevent a significant reduction in S/N due to loss in RF cables connecting the antenna to a receiver.

The antenna can also be used as a feed for the R&S®AC008 microwave directional antenna.

## **Key facts**

- Wide frequency range
- Selectable broadband preamplifiers
- I Simultaneous reception of both polarization planes
- No reduction in S/N due to the use of low-noise amplifiers at the antenna outputs
- Usable as a feed for R&S®AC008 microwave directional antenna



Specifications	
Frequency range	1 GHz to 18 GHz
Polarization	horizontal and vertical (simultaneously)
Input impedance	50 Ω
VSWR	< 3
Antenna gain (passive)	typ. 6 dBi
Noise figure	max. 3.6 dB
Practical gain (active)	typ. 36 dB
1 dB compression point	min. +5 dBm

Power supply	+15 V DC (max. 0.7 A) (preamplifier), +12 V DC (max. 1 A) (switching network)
Connector	2 × SMA female
Control connector	10-contact, round, male
MTBF	> 55 000 h
Operating temperature range	−30°C to +55°C
Dimensions ( $\emptyset \times H$ ; with radome)	approx. 210 mm $\times$ 390 mm (8 in $\times$ 15 in)
Weight	approx. 1.7 kg (4 lb)

Ordering information	Туре	Order No.
Crossed Log-Periodic Antenna	R&S°HL024S8	4042.7509.02
Recommended extras		
Control Unit	R&S°GB016	4056.7006.03
Control Cable, length: 10 m	R&S°GB016Z1	4056.7270.02
Microwave Cable, length: 5 m	R&S®AC008W2	0751.6931.04
Microwave Cable, length: 10 m	R&S®AC008W2	0751.6931.05
Adapter for R&S®HZ-1	R&S®HL025Z1	4053.4006.03
Wooden Tripod	R&S®HZ-1	0837.2310.02

